

**K.S. GROUP OF INSTITUTIONS**  
**K.S. SCHOOL OF ENGINEERING & MANAGEMENT**

# 15, Mallasandra, Near Vajarahalli, Off. Kanakapura Road, Bengaluru- 560 109  
 www.kssem.edu.in



**KSSEM**  
 K.S. SCHOOL OF ENGINEERING AND MANAGEMENT

## BLUE BOOK

Name of the Student: Nida Manzoor Jeli

Class / Sem : 8<sup>th</sup> Branch: civil

USN : 

1	K	G	2	0	C	V	0	0	5
---	---	---	---	---	---	---	---	---	---

SUBJECT: Design of Pre-stressed concrete elements Subject Code: 18CV81

**MAXIMUM MARKS :**

Test	I	II	III	Average Marks Obtained
Date	12-4-24	6-5-24	13-5-24	$\frac{30}{30} + 10 = \frac{40}{40}$
Marks Obtained	30	30	30	
Signature of the Student	Nida	Nida	Nida	Nida
Initials of Room Supervisor	pe	pe	pe	
Initials of Faculty	pe	pe	pe	pe

NAME OF FACULTY : Dr. Nana M

Makelle

SIGNATURE : pe

SIGNATURE OF H.O.D.

# K S SCHOOL OF ENGINEERING AND MANAGEMENT

## First Internal test

Q. No	Marks	CO	Q. No	Marks	CO	CO	Total
1(a)	10	1	3(a)			1	20
1(b)	5	2	3(b)				
1(c)			3(c)			2	10
OR		OR					
2(a)			4(a)	10	1	Grand Total	30
2(b)			4(b)	5	2		
2(c)			4(c)				

## Second Internal test

Q. No	Marks	CO	Q. No	Marks	CO	CO	Total
1(a)	10	2	3(a)			2	10
1(b)	5	2	3(b)				
1(c)			3(c)			3	20
OR		OR					
2(a)			4(a)	10	3	Grand Total	30
2(b)			4(b)	5	2		
2(c)			4(c)				

## Third Internal test

Q. No	Marks	CO	Q. No	Marks	CO	CO	Total
1(a)	10	4	3(a)			4	20
1(b)	5	5	3(b)				
1(c)			3(c)			5	10
OR		OR					
2(a)			4(a)	10	4	Grand Total	30
2(b)			4(b)	5	5		
2(c)			4(c)				

  
 Signature of the Staff



**K.S. SCHOOL OF ENGINEERING AND MANAGEMENT, BANGALORE - 560109**  
**DEPARTMENT OF CIVIL ENGINEERING**  
**SESSION: 2023-2024 (EVEN SEMESTER)**  
**I SESSIONAL TEST QUESTION PAPER**  
**SET-B**

USN 

--	--	--	--	--	--	--	--	--	--

Degree : B.E  
Branch : Civil Engineering  
Course Title : Design of Pre stressed concrete Elements  
Duration : 90 Minutes

Semester : VIII  
Course Code : 18CV81  
Date : 12/04/2024  
Max Marks : 30

**Note: Answer ONE full question from each part.**

Q No.	Question	Marks	K-Level	CO mapping
<b>PART-A</b>				
1(a)	<b>Explain</b> the necessity of high strength concrete and high strength steel is used in Pre stress concrete.	5	<b>K2</b> Understanding	CO1
(b)	<b>Explain</b> the advantages of PSC over RCC.	5	<b>K2</b> Understanding	CO1
(c)	<b>Explain</b> the various types of losses in Pre-Tensioning system.	5	<b>K2</b> Understanding	CO2
<b>OR</b>				
2(a)	<b>Explain</b> with sketch the Hoyer's Long line system of pre-tensioning.	5	<b>K2</b> Understanding	CO1
(b)	<b>Explain</b> the difference between Pre-Tensioning and Post Tensioning system.	5	<b>K2</b> Understanding	CO1
(c)	<b>Explain</b> the various types of losses in Post-Tensioning system.	5	<b>K2</b> Understanding	CO2
<b>PART-B</b>				
3(a)	A prestressed concrete beam made of T section has a flange of (1000mmX150mm) and web of (200X800mm). Beam supports super imposed load of 180kN/m over a simply supported over a span of 8m. If the prestressing force in the tendon is 6200kN at mid span and is located at a distance of 500mm from soffit. <b>Determine</b> the resultant stress at midspan for the following case. i) Prestress+Self-weight ii) Prestress+Self-weight+Live load Assume Density of concrete is 24kN/m <sup>3</sup>	10	<b>K3</b> Applying	CO1
(b)	A simply supported pre stressed concrete beam spanning over 10m is of rectangular section 200mm wide and 300mm deep is prestressed with wires area=320mm <sup>2</sup> , locate at a constant eccentricity of 50mm and carrying a initial stress of 1000N/mm <sup>2</sup> . The beam is pretensioned. <b>Determine</b> the loss of stress in wires using the following data. $E_s=210kN/mm^2$ , $E_c=35kN/mm^2$ , Relaxation of steel stress=5% of initial stress, shrinkage of concrete=300*10 <sup>-6</sup> , Creep coefficient=1.6.	5	<b>K3</b> Applying	CO2

OR

4(a)	A prestressed concrete beam of section 200mm wide by 300mm deep is used over a effective span of 6m to support an imposed load of 4kN/m. The density of concrete is 24kN/m <sup>3</sup> . <b>Determine</b> the magnitude of concentric prestressing force necessary for zero fibre stress at the soffit when the beam is fully loaded.	10	K3 Applying	CO1
(b)	A pre stressed concrete beam spanning over 10.5 m is of rectangular section 300X600 is prestressed with wires area=800mm <sup>2</sup> , locat at a constant eccentricity of 100mm and carrying a initial stress of 1050N/mm <sup>2</sup> . The beam is pretensioned. <b>Determine</b> the loss of stress in wires using the following data. $E_s=210\text{kN/mm}^2$ , $E_c=35\text{kN/mm}^2$ , Relaxation of steel stress=2.5% of initial stress, shrinkage of concrete= $300 \times 10^{-6}$ , Creep coefficient=1.6.	5	K3 Applying	CO2


(S)

  
Course Incharge

  
HOD CV

Professor & Head  
Dept. of Civil Engineering  
K.S. Group of Institutions  
K.S. School of Engineering & Management  
Bangalore-560 062.

  
IQAC- Coordinator

  
Principal

Dr. K. RAMA NARASIMHA  
Principal/Director  
K S School of Engineering and Management  
Bengaluru - 560 109